

폴리우레탄 싱크로 벨트 표준길이표

T5형

피치 : 5.0mm

T10형

피치 : 10.0mm

호 칭	피치원주 (mm)	잇수	R	u
T5-165	165.0	33	-	●
T5-185	185.0	37	-	●
T5-200	200.0	40	-	●
T5-215	215.0	43	-	●
T5-220	220.0	44	-	●
T5-225	225.0	45	-	●
T5-245	245.0	49	-	●
T5-250	250.0	50	-	●
T5-255	255.0	51	-	●
T5-260	260.0	52	-	●
T5-270	270.0	54	-	●
T5-275	275.0	55	-	●
T5-280	280.0	56	-	●
T5-295	295.0	59	-	●
T5-300	300.0	60	-	●
T5-305	305.0	61	-	●
T5-325	325.0	65	-	●
T5-330	330.0	66	-	●
T5-340	340.0	68	-	●
T5-350	350.0	70	-	●
T5-355	355.0	71	-	●
T5-365	365.0	73	-	●
T5-375	375.0	75	-	●
T5-390	390.0	78	-	●
T5-400	400.0	80	-	●
T5-410	410.0	82	-	●
T5-420	420.0	84	-	●
T5-425	425.0	85	-	●
T5-450	450.0	90	-	●
T5-455	455.0	91	-	●
T5-465	465.0	93	-	●
T5-475	475.0	95	-	●
T5-480	480.0	96	-	●
T5-500	500.0	100	-	●
T5-510	510.0	102	-	●
T5-525	525.0	105	-	●
T5-545	545.0	109	-	●
T5-550	550.0	110	-	●
T5-560	560.0	112	-	●
T5-575	575.0	115	-	●
T5-600	600.0	120	-	●
T5-610	610.0	122	-	●
T5-620	620.0	124	-	●
T5-630	630.0	126	-	●
T5-640	640.0	128	-	●
T5-650	650.0	130	-	●
T5-660	660.0	132	-	●
T5-675	675.0	135	-	●
T5-690	690.0	138	-	●
T5-695	695.0	139	-	●
T5-700	700.0	140	-	●
T5-720	720.0	144	-	●
T5-750	750.0	150	-	●
T5-780	780.0	156	-	●
T5-800	800.0	160	-	●
T5-815	815.0	163	-	●
T5-840	840.0	168	-	●
T5-850	850.0	170	-	●
T5-900	900.0	180	-	●
T5-940	940.0	188	-	●
T5-990	990.0	198	-	●
T5-1000	1000.0	200	-	●
T5-1075	1075.0	215	-	●
T5-1100	1100.0	220	-	●
T5-1140	1140.0	228	-	●
T5-1215	1215.0	243	-	●
T5-1380	1380.0	276	-	●
T5-1440	1440.0	288	-	●

호 칭	피치원주 (mm)	잇수	R	u
T10-260	260.0	26	-	●
T10-370	370.0	37	-	●
T10-400	400.0	40	-	●
T10-410	410.0	41	-	●
T10-440	440.0	44	-	●
T10-450	450.0	45	-	●
T10-500	500.0	50	-	●
T10-530	530.0	53	-	●
T10-560	560.0	56	-	●
T10-610	610.0	61	-	●
T10-630	630.0	63	-	●
T10-660	660.0	66	-	●
T10-690	690.0	69	-	●
T10-700	700.0	70	-	●
T10-720	720.0	72	-	●
T10-750	750.0	75	-	●
T10-780	780.0	78	-	●
T10-810	810.0	81	-	●
T10-840	840.0	84	-	●
T10-880	880.0	88	-	●
T10-890	890.0	89	-	●
T10-900	900.0	90	-	●
T10-920	920.0	92	-	●
T10-960	960.0	96	-	●
T10-970	970.0	97	-	●
T10-980	980.0	98	-	●
T10-1000	1000.0	100	-	●
T10-1010	1010.0	101	-	●
T10-1080	1080.0	108	-	●
T10-1100	1100.0	110	-	●
T10-1110	1110.0	111	-	●
T10-1140	1140.0	114	-	●
T10-1150	1150.0	115	-	●
T10-1210	1210.0	121	-	●
T10-1240	1240.0	124	-	●
T10-1250	1250.0	125	-	●
T10-1300	1300.0	130	-	●
T10-1320	1320.0	132	-	●
T10-1350	1350.0	135	-	●
T10-1390	1390.0	139	-	●
T10-1400	1400.0	140	-	●
T10-1420	1420.0	142	-	●
T10-1440	1440.0	144	-	●
T10-1450	1450.0	145	-	●
T10-1460	1460.0	146	-	●
T10-1500	1500.0	150	-	●
T10-1560	1560.0	156	-	●
T10-1610	1610.0	161	-	●
T10-1750	1750.0	175	-	●
T10-1780	1780.0	178	-	●
T10-1880	1880.0	188	-	●
T10-1960	1960.0	196	-	●
T10-2250	2250.0	225	-	●

T2.5형

피치 : 2.5mm

호 칭	피치원주 (mm)	잇수	R	u
T2.5-120	120.0	48	-	●
T2.5-145	145.0	58	-	●
T2.5-160	160.0	64	-	●
T2.5-177.5	177.5	71	-	●
T2.5-200	200.0	80	-	●
T2.5-230	230.0	92	-	●
T2.5-245	245.0	98	-	●
T2.5-265	265.0	106	-	●
T2.5-285	285.0	114	-	●
T2.5-305	305.0	122	-	●
T2.5-317.5	317.5	127	-	●
T2.5-330	330.0	132	-	●
T2.5-380	380.0	152	-	●
T2.5-420	420.0	168	-	●
T2.5-480	480.0	192	-	●
T2.5-492.5	492.5	197	-	●
T2.5-500	500.0	200	-	●
T2.5-600	600.0	240	-	●
T2.5-620	620.0	248	-	●
T2.5-650	650.0	260	-	●
T2.5-780	780.0	312	-	●
T2.5-915	915.0	366	-	●
T2.5-950	950.0	380	-	●